

## External Corner Tape

### Item Code and Description

- a. WP3201-INT . . . External Corner—1 corner
- b. WP3212-INT . . . External Corner—12 corners

### General Product Description

- a. a rugged, flexible, preformed corner tape for covering joints to prevent penetration of moisture and provide a sound foundation for tile or stone overlayers
- b. anti-fracture protection between substrates and hard surface coverings
- c. embed with TANK/10® waterproofing compound

### Physical Characteristics

- a. preformed for external corners
- b. substrate: modified polyester knit fabric
- c. coating: thermoplastic elastomere with nonwoven polypropylene
- d. color: blue with white mesh edges
- e. width: 4¾" overall; 1" mesh edges; 2¾" center
- f. length: 11" overall; 5½" each leg
- g. thickness: approximately 1mm

### Performance Characteristics

- a. a flexible tape for embedment over external corner joints
- b. impermeable center polyester (blue) areas
- c. bonds well with TANK/10® waterproofing compound
- d. use to cover joints between ARC TrueDEK™ shower foundations and surrounding tile backer, and to cover joints between tile backer panels
- e. use where three surfaces interface at 90°
- f. fill gaps beneath tape that are 1/8" wide or more using latex caulk or thinset mortar (do not use silicone)
- g. remove all dirt, debris, and contaminants from surfaces prior to embedding tape
- h. surfaces must be completely dry before embedding tape
- i. tape is not designed as a wear surface; cover with tile, stone, or other appropriate material
- j. material safety data sheet available on request

### Compliance

- a. ICC PMG-1248 lists compliance with:
  1. 2015, 2012 and 2009 International Residential Code® (IRC)
  2. 2015, 2012 and 2009 International Plumbing Code® (IPC)
  3. 2015, 2012 and 2009 Uniform Plumbing Code® (UPC)
  4. 2010 and 2005 National Plumbing Code of Canada (NPC)
  5. ANSI A118.10-2008 American National Standard Specification for Load Bearing, Bonded, Waterproof Membranes for Thin-Set Ceramic Tile and Dimension Stone Installation
  6. ICC-ES AC 115-2008 Acceptance Criteria for Waterproof membranes for Flooring and Shower Lining



### Other Information

- a. manufacturer warrants to the original owner of the property where product is installed that joint reinforcement tape and gaskets shall be free from defects in the material when properly applied for a period of five years

# External Corner Tape

