

Item Code and Description

- a. WP2112-TNK . . . TANK/10[®] Adhesive — Bulk carton

General Product Description

- a. a ready-to-use polyurethane construction adhesive
- b. for interior and exterior applications
- c. 12 tubes per carton
- d. TANK/10[®] Adhesive provides a superior bond between many materials, including plastic, fiberglass, wood, and engineered wood products

Physical Characteristics

- a. polyurethane base
- b. volume: 10.48 fl. oz. (310ml) per tube/12 tubes per carton
- c. color: gray
- d. low odor
- e. highly tacky and quick bonding
- f. VOCs: 34 g/L less water and exempt compounds. Use product as supplied.

Performance Characteristics

- a. Tank/10 Polyurethane Construction Adhesive and Sealant is a fast setting, fast curing formula for interior and exterior applications. This adhesive/sealant provides a superior bond between most building materials, including ARC shower bases, solid wood and engineered wood joists, and plywood and OSB subfloor materials. Tank/10 Adhesive also bonds many plastics, most wood products, glass, metal, concrete, masonry and other materials. Tank/10 can be used as an adhesive and as a sealant.
- b. dispense adhesive with caulk gun
- c. coverage: 30 lineal ft. of 1/4" bead
- d. application temperature: -40° F to 194° F
- e. adhesive skins over in approximately 50 to 90 minutes
- f. clean surfaces and tools with mineral spirits while adhesive remains wet
- g. may be used as a sealant
- h. 14 month shelf life from the time of manufacture
- i. keep out of reach of children
- j. material safety data sheet available on request

Directions

- a. surfaces must be clean and free of any material that may prevent adhesion
- b. cut tip at a slant to dispense a 1/4" to 3/8" thick bead
- c. puncture inner seal
- d. load cartridge into caulking gun
- e. apply beads of adhesive to one surface
- f. press surfaces together. For ARC shower base installations, apply adhesive generously to joists or subfloor. In general, apply adhesive to areas no larger than one shower base or 4'x8' sheet of subfloor at a time so that adhesive does not skin over before surfaces are pressed together. Fasten materials according to manufacturer's instructions.

Warning

- use only with adequate ventilation
- avoid prolonged or repeated contact with skin or inhalation of vapors
- do not allow eye contact
- do not ingest
- may cause serious eye irritation or skin irritation
- wearing protective equipment, like gloves and a respirator, is always recommended

Hazards

- causes serious eye irritation
- causes skin irritation
- may cause allergy or asthma symptoms or breathing difficulties if inhaled
- may cause an allergic skin reaction
- suspected of causing cancer
- causes damage to sensory organs
- causes damage to nervous system and sensory organs through prolonged or repeated exposure

Other Information

- LIMITED WARRANTY:** ARC, Inc. warrants that this product meets the applicable product specifications at the time it is shipped. This product is intended for the purposes described above. ARC makes no other express or implied warranties or conditions, including any implied warranty or condition of merchantability or fitness for a particular purpose. If this ARC product does not conform to this warranty, the sole and exclusive remedy is, at ARC's option, replacement of the ARC product or refund of the purchase price. Except where prohibited by law, ARC will not be liable for any loss or damage arising from the ARC product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

