

MiniDEK®

Item Code and Description

- a. 21001
- b. 16" × 16" MiniDEK base

General Product Description

- a. prefabricated, tileable, structural, pre-sloped shower receptor
- b. cover with decorative tile, stone, or weldable resilient flooring
- c. suitable for laundry room floor drain, pet shower drain, outdoor shower drain, secondary drain for bathroom, mechanical room drain

Physical Characteristics

- a. made of fiberglass reinforced plastic (GRP)
- b. spans 16" o.c. joist systems
- c. edges are 9/16" thick
- d. drain hole diameter is 61/4"
- e. four gradient planes
- f. gradients are 2% per foot or greater
- g. centered drain hole
- h. pre-bored, countersunk pilot holes
- i. color: blue
- j. weight: approximately 9 lbs.
- k. made from 100% recyclable materials

Performance Characteristics

- a. pre-pitched foundation for drain construction
- b. install on wood or engineered joist systems, on subfloor, or on concrete
- c. cut and drill as needed with standard power tools
- d. may be trimmed on all sides (remain at least 6" from drain hole)
- e. rated to carry a 840 lb. load when installed on proper joists spaced 16" o.c. supplemented with perimeter and drain hole blocking (increase load capacity with additional blocking and support)
- f. complete installation requires a Classic Drain Assembly and waterproofing materials
- g. remove tile, redo waterproofing, and re-tile without damaging foundation

Compliance

- a. ICC PMG-1223 lists compliance with:
 - 1. 2015, 2012 and 2009 International Residential Code® (IRC)
 - 2. 2015, 2012 and 2009 International Plumbing Code® (IPC)
 - 3. 2015, 2012 and 2009 Uniform Plumbing Code® (UPC)
 - 4. 2010 and 2005 National Plumbing Code of Canada (NPC)
 - 5. IAPMO PS106-2015e1 for prefabricated, tileable shower receptors
 - 6. CSA B45.5/IAPMO Z124-2011, Plastic Plumbing Fixtures
- b. QAI Laboratories test report no. RJ4241-1
 - 1. meets conditions of classification for 30-minute flame spread index and smoke developed index per ASTM E84 requirements





Other Information

a. AKW limited lifetime warranty



MiniDEK®





