

## Acrylic Latex Caulk

### Item Code and Description

- a. 4010-PAC . . . Painters Acrylic Latex Caulk — Bulk carton

### General Product Description

- a. a ready-to-use, easy-to-apply latex caulk for interior applications
- b. 6 cartridges per carton
- c. made by Titebond

### Physical Characteristics

- a. latex, acrylic base (no silicone content)
- b. volume: 10.1 fl. oz. per cartridge
- c. color: white
- d. low odor
- e. highly tacky, quick bonding, and fast drying
- f. bonds to most building materials
- g. working time: 10-15 minutes
- h. non-reactive VOC: 23 g/L (<1.5%)
- i. ASTM C834 TYPE OP GRADE -18°C

### Performance Characteristics

- a. Surfaces must be cleaned down to the original substrate, dry and free from oil, grease, water, dirt or any other material that may prevent adhesion
- b. dispense adhesive with caulk gun
- c. paintable
- d. coverage: 123 linear feet with a 1/8" bead
- e. application temperature: above 40° and below 120°
- f. adhesive skins over in approximately 30 minutes; cures in 2 to 4 hours
- g. clean surfaces and tools with water while adhesive remains wet
- h. may be used as a sealant
- i. 24 month shelf life from the time of manufacture for an unopened, completely sealed cartridge
- j. keep out of reach of children

